



Spotting Boards

Models 44SP/44SPG



Model 44SP

- Heated air for faster drying
- Integrated vacuum available
- Unique design assures no steam leaks
- Available with stainless steel or glass top
- Fabric catch rack swivels to hold garments while spotting
- Foot pedals allow operator to control flow of steam, air and vacuum

www.forentausa.com

Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

Specifications

Models 44SP / 44SPG

Steam and Air connection		44SP/44SPG
Steam Inlet	NPT	1/2"
Steam Outlet	NPT	1/2"
Recommended steam pressure	PSIG	75-85
	kPa	517-586
Steam consumption @ 80psig(552 kPa)	BHP	1
	kg/hr	15.6
	lb/hr	34.5
Compressed air	NPT	1/2"
Air consumption	free air/cycle at 80psig	3.0 cu.ft.
	free air/cycle at 552kPa	85 liters
Recommended air pressure	PSIG	80
	kPa	552
Air Vacuum Connection	NPT	1 1/4"
Optional Vacuum Motor Attachment Electrical		
Voltage: 110-120VAC, 1PH, 60Hz, 8.1 Amps (Cord Connected)		
Voltage: 220VAC, 1PH, 60Hz, 4.1 Amps (Cord Connected)		
Weight (crated)		
Shipping	lbs	244
	kg	111
1 Steam Connection	3 Air Connection	5 Optional Vacuum motor
2 Steam Outlet	4 Air Vacuum Connection	6 Vacuum On/Off Switch

Detail Line Drawing

(millimeters shown in parentheses)

